

INSTALLATION GUIDE

SIGNUM ventilation outlet tile



1

Use the lid of the box, designed as a template, to cut out the underlay.

Separate the template according to the desired diameter. To do this, press in the pre-pressed (perforated) circles!



2

Adjust the template to the correct position with the help of the OUTLET tile and GLUE it to the underlay.

Mark the location of the cut on the UNDERLAYMENT (along the outer edge of the template).



3

Cut the underlay along the mark using a safety knife.

Always use a rigid formwork below the outlets to support the underlay connection bushing.

Cut this formwork using a drill.



4

Thread the bottom ring clockwise beneath the underlay. To do so, align the notch on the ring to the spot that has been cut and twist the entire ring into place.



5

The top ring can be mounted with or without the rubber flange.

Press the top ring onto the bottom one until you hear a click.



6

Mark the diameter of the SIGNUM pipe on the rubber flange and cut it along the pre-made groove.



7

The vent pipe can be connected using the provided flexible pipe, which must be passed through the hole of the adapter or connected directly from the inside. The flexible pipe must be positioned with a slope so that any condensation can be drained.

Depending on the regulations on connections and the layer structure of the roof this can be introduced using a commercially available HT pipe or directly with the plastic adapter on SIGNUM.

A notice:

- The specifications of national regulations (such as ZVDH, ÖNORM or SIA standards) as well as national and European standards (such as DIN or EN) must be kept.
- The installer is responsible for the processing and installation of the products in accordance with the assembly instructions and the resulting tightness in the sub-roof. CREATON South-East Europe Kft. has no responsibility for damage caused by improper installation.
- CREATON South-East Europe Ltd. assumes no liability for damages resulting from improper installation.



8

According to the application the SIGNUM 100 outlet can be left open or closed at its top. This can be done by unscrewing the cover at the end of the pipe.

In the case of SIGNUM 125 remove or leave the middle of the cover in place according to the application.